

CLAIMS

1. In a Java computing environment, a Java object representation
suitable for use by a Java virtual machine, said a Java object representation
5 comprising:

a first reference to an internal class representation of said Java
object;

a second reference to instance fields associated with said Java
object; and

10 wherein said first reference is a direct reference to said internal class
representation of said Java object.

2. A Java object representation as recited in claim 1,

wherein said second reference is a reference to an array of
15 references, and

wherein each reference in said array of references is a reference to
an instance field associated with said Java object.

3. A Java object representation as recited in claim 1, wherein said first
20 reference is allocated as four bytes.

4. A Java object representation as recited in claim 1, wherein said
second reference is allocated as four bytes.

25 5. A Java object representation as recited in claim 1,
wherein said internal class representation includes a header of a
predetermined size, and

wherein a method table associated with said Java object is allocated immediately after said header.

6. A Java object representation as recited in claim 1, wherein said Java
5 object representation further comprises:

a hash key that can be used to identify the Java object.

7. A Java object representation as recited in claim 6, wherein said hash
key is the memory address of said first reference.

10

8. A method for representing a Java object in a virtual machine, said
method comprising:

allocating a first reference in a memory portion of said virtual
machine, wherein said first reference is a reference to an internal class
15 representation of said Java object;

allocating a second reference in a memory portion of said virtual
machine, wherein said second reference is a reference to instance fields
associated with said Java object; and

wherein said first reference is a direct reference to said internal class
20 representation of said Java object.

9. A method as recited in claim 8,

wherein said second reference is a reference to an array of
references, and

25 wherein each reference in said array of references is a reference to
an instance field associated with said Java object.

10. A method as recited in claim 9, wherein said first reference is allocated as four bytes.

11. A method as recited in claim 9, wherein said second reference is
5 allocated as four bytes.

12. A method as recited in claim 9,
wherein said internal class representation includes a header of a predetermined size, and
10 wherein a method table associated with said Java object is allocated immediately after said header.

13. A method as recited in claim 9, wherein Java object representation further comprises:
15 storing a hash key that represents the object.

14. A method as recited in claim 9, wherein said hash key is the memory address of said first reference.

20 15. A method of accessing information regarding a Java object, said method comprising:
identifying an object representation associated with said Java object;
using a first reference in said object representation to locate an appropriate internal class representation associated with said Java object;
25 accessing information regarding said Java object from said internal class representation; and
wherein said object is represented in a Java virtual machine.

16. A method as recited in claim 15, wherein said method further comprises:

5 skipping a header of said internal class representation to access a method table associated with said Java object.

17. A method as recited in claim 15, wherein said information regarding said Java object includes a field descriptor table.

10 18. A computer readable media including computer program code for a Java object representation suitable for use by a Java virtual machine, said computer readable media comprising:

computer program code for a first reference to an internal class representation of said Java object;

15 computer program code for a second reference to instance fields associated with said Java object; and

wherein said first reference is a direct reference to said internal class representation of said Java object.

20 19. A computer readable media as recited in claim 18,

wherein said second reference is a reference to an array of references, and

wherein each reference in said array of references is a reference to an instance field associated with said Java object.

25 20. A computer readable media as recited in claim 18, wherein said computer readable media further comprises:

computer program code for a hash key for the Java object.